



CLEAR 8 C

Clear 8 C films help secure your windows by ensuring that the glass does not shatter, remaining transparent and retaining its overall integrity in the event of an impact, explosion or fire. Comply with European Standard EN 12600.



Warranty
10 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



European Standard EN 12600
1B1



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

- ↔ **122 cm**
- ↔ **152 cm**
- ↔ **183 cm**

TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	5 %
Visible light transmission	83 %
Reflection of external visible light	10 %
Reflection of internal visible light	10 %
Total solar energy rejected	20 %
Total solar energy rejected 2*	21 %
Solar ratio :	
Solar energy reflection	10 %
Solar energy absorption	14 %
Solar energy transmission	76 %
Reduction in Solar Glare	15 %
g-value	0.82
u-value	5.7
Shading coefficient	0.9
Tensile strength (kg/cm ²)	40
Elongation at break	125%
Installation type : Interior	
Roll length	30,5 m
Film composition	PET
Thickness	240 µ

Colour from the outside :
 TRANSPARENT

CONSTRUCTION

- "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- High optical quality polyester
- Bonding adhesive
- High optical quality polyester
- Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
- Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

Non-contractual data. We reserve the right to modify the composition of our films at any time. Consult our warranty documents.